

**WWW.
BKPARKET
.COM**

PRODUCTION

BK PARKET s.r.o.
Pravenec 433
972 16 Pravenec
Slovakia

SALE

SHESTR s.r.o.
G. Švéniho 10A
971 01 Prievidza
Slovakia

INFO@BKPARKET.COM
+421 918 633 633



**WOODEN
PARQUET
BOARD FLOOR**

WWW.BKPARKET.COM



HAVE A PIECE OF NATURE AT HOME

Your choice will be easy if you get inspired by the beauty of the wood. This material is original and unique because it has been offered by the nature itself. Since ancient times, oak trees have been celebrated for their size, durability and especially for their hard and beautiful wood.

Company BK PARKET, s.r.o. has operated both on Slovak and international market since 1997 and deals with the development, production and sale of wooden floors. We have joined innovation, tradition and customer-oriented company policy and thus moved forward with the aim of satisfying our need of our customers and company partners.

First-rate selection of materials and usage of new technologies help us to ensure perfection during wood-processing. Solid and honest production enables us to reach our goals and retain top international standards.

illustration photo: large-area three-layered parquet, 20 mm honey oak, rustic



NATURE DID HER PART, WE
TOOK CARE OF THE REST



RESIDENTIAL COLLECTION

LARGE-AREA SINGLE PLANKS

Boards that represent home – comfort, style and beauty of your life

Originality of our floors is given by the nature itself – by size, structure and age of the trees. With regard to the yield and further processing we produce wooden floors in various lengths up to 2,200 mm. Segments of various lengths are a part of each delivery, and as such create wooden floor that does not look monotonous. On the contrary, they support its visual uniqueness, exclusivity and natural look.

BK PARKET as a producer of wooden floors offers the choice from various constructions - three-layered or full-massive. Are you looking for a floor suitable for under floor heating? We have a solution for this – a certified collection for under floor heating.



LARGE-AREA THREE-LAYERED PARQUET 15 MM

Single plank, oiled
Thickness 15mm, width 180mm
Length 700-2150mm
Wear layer:4mm
Connection: groove and tongue



LARGE-AREA THREE-LAYERED PARQUET 20 MM

Single plank, oiled
Thickness 20mm, width 180mm
Length 700-2150mm
Wear layer:6mm
Connection: groove and tongue



UNDER FLOOR HEATING PROGRAMME

Single plank, oiled
Thickness 12mm, OAK-OAK-OAK
Width 138mm, length 1100mm
Wear layer:4mm Connection: groove and tongue
Certified floor suitable for using with
under floor heating



FULL-MASSIVE COLLECTION

Single plank, oiled
Thickness 20mm, width 152mm
Length 700-2150mm
Connection: groove and tongue

CHEVRON

RETRO DESIGN

Fancy spending time at home? Follow the newest European trends. Return to natural materials and historic heritage of art of wood processing in connection with current technological progress and new ideas.

CHEVRON

130 mm x 500 mm x 14 mm
60 degree angle
4mm oak wear layer
10mm spruce/birch plywood



CHEVRON STRIPPING

130 mm x 500 mm x 14 mm
130 mm x 1500 mm x 14 mm STRIPP
60 degree angle
4mm oak wear layer
10mm spruce/birch plywood



illustration photo: Chevron, oak graffit, prime

RETRO DESIGN

HERRINGBONE

Suitable for both modern and traditional interiors. This type of floor intensifies the effect of unique harmony of space and furniture in modern interiors and underlines antique and rustic character of classical interiors.



ilustračné foto Herringbone, prime

HERRINGBONE



130 mm x 390 mm x 15 mm

4mm oak wear layer

9mm spruce blockboard

2mm spruce ply



illustration photo: Herringbone, prime



illustration photo Copenhagen, honey oak, prime

BRIQUETTE




COPENHAGEN



DUTCH



BRODERIE



TISSAGE



MOULIN



MARELLE



ECHELLE



CHECKERS



Setting

BRODERIE, TISSAGE, MOULIN, MARELLE, CHECKERS
contain square 130 x 130mm x 15 mm

Setting

ECHELLE contains STRIP 130mm x 1500mm

COLLECTION

STYLE

SURFACE PROCESSING



REAL WOOD



BRUSHED



LONGITUDINAL
MICRO-SHRINKAGE



ECO FRIENDLY



ANTISTATIC SURFACE
TREATMENT



R10 ANTI-SLIP
CLASS

Collection Style dominates by slightly brushed planks in fashionable colours that fit into each type of interior.

loors in the collection Style have 2V longitudinal micro-shrinkage

Shades of this collection may be applied to all constructions of RESIDENTIAL COLLECTION and RETRO DESIGN.

Haven't you found a shade of your dreams? The producer hereby offers the possibility of creating your own colour shade in accordance with your requirements.

Due to the use of massive wood that is naturally varied in colour and structure we cannot guarantee a 100% identity of all planks. Colour and structure of wood may vary from reality.

OAK GRAFFIT

OAK ALASKA

OAK LATTE

OAK PALISANDER

OAK COGNAC

OAK HONEY



illustration photo – under floors heating programme oak honey, prime



COLLECTION

EXCLUSIVE

SURFACE PROCESSING



REAL WOOD



BRUSHED



LONGITUDINAL AND
TRANSVERSE MICRO-
SHRINKAGE



ECO FRIENDLY



ANTISTATIC SURFACE
TREATMENT



R10 ANTI-SLIP
CLASS



illustration photo: large-area parquet
three-layered 15mm smoke oak, rustic

Beauty of wood structure is enhanced by brushing.

Floors in the collection Exclusive have 4V longitudinal and transverse micro-shrinkage.

Technology of smoking used in decors SMOKE OAK and PEARL OAK creates colourful uniqueness of each plank and as such accentuates the natural authenticity of the wood. The technology of smoking results in colour varieties which are not considered wood defects, but on the contrary, they show the true nature of wooden floor.



Collection Exclusive represents the combination of precise production and art in surface treatment. Combinations of multiple production operations create a unique experience that will enhance the interior design.

Shades of Exclusive collection may be applied to all constructions of RESIDENTIAL COLLECTION and RETRO DESIGN.

Haven't you found a shade of your dreams? The producer hereby offers the possibility of creating your own colour shade in accordance with your requirements.

Due to the use of massive wood that is naturally varied in colour and structure we cannot guarantee a 100% identity of all planks. Colour and structure of wood may vary from reality.



OAK VELVET



OAK SNOW



OAK COUNTRY



OAK SMOKE



OAK PEARL



OAK GOTHIC

SELECTION OF CUT TIMBER

When choosing construction and surface treatment of your future floor, you may choose from two classes of cut timber that characterize natural structure and features of the wood.

Knots up to 50 mm sealed, sap allowed. Colour varieties allowed.

CLASS RUSTIC



*illustration photo: large-area parquet
three-layered 20mm oak Gothic, rustic*



*illustration photo: large-area parquet
three-layered 15mm oak Snow, prime*



Perfectly beautiful imperfection of wood makes the interior vivid, naturally warm and charming.

Face and atmosphere of home speaks about life attitudes and relation of the owners to the world around them. Just as our life is unrepeatable and unique, our home, the most intimate space we live in, is also unique. This is the stage on which we play the part in the theatre of life, those are the boards that mean home.

CLASS PRIME

Grains and knots up to 5mm sealed, no sap allowed.
Minimum colour varieties allowed.

OAK/BEECH, DOUBLE-PLANK, VARNISHED BY UV OIL

Thickness 22mm, width 132 mm,
length 2400 mm, connection: groove and tongue
Varnishing: BEECH - 4 layers/OAK - 5 layers
Type of varnish: acrylic UV

illustration photo: OAK



REAL WOOD



PEFC
ECO FRIENDLY



BRUSHED



ANTISTATIC
TREATMENT



POSSIBILITIES OF USE

Indoor sports centres
Squash centres
Dance floors

SPORT

MASSIVE DANCE FLOOR

Sports certified floor with the
possibility of production of large-area
boards. Suitable also for dance
purposes.



illustration photo: sport massive, varnished by UV oil

PHILOSOPHY AND ECOLOGY

Company BK Parket as a producer of wooden flooring always acts in compliance with the strictest criteria and resolutions in terms of ecology and sustainability of forest treatment.

We are a producer that has been certified by PETC. This means that the sources of our input raw material come from suppliers who also have to comply with the strictest criteria of COC customer chain.

Through COC certificate we fully guarantee the origin of our wood material. Even in the production process we only use certified and approved products from EU suppliers.

The year 2012 was an important milestone in our company. We installed photovoltaic panels and thus lowered CO2 emissions by using electric energy from sun heating.

SURFACE TREATMENT BY OILING OXY OIL

A colouring oil for treating deciduous and coniferous wood has a very good penetration and waterproof features. It improves the natural structure of wood and shows elegant wood colouring. Solidifies through oxygen binding (oxidative drying).

Content

Modified natural oils, waxes, silicic acid, slightly aromatic isoparaphines, non-lead and non-cobalt drying agent.

Carrying capacity

Fully carrying-capable after 7 days.

Warning

Oiled wooden floors must be cleaned and treated only by specially designed products from various producers. Please, consult the salesman before you choose the product and adhere to the enclosed instruction.

Recommendation

Oiled wooden floors should be periodically treated by applying oxidative and/or hard wax oil every 1-2 years according to the carrying capacity of the floor. Exposed areas with increased carrying capacity should be treated by hard wax oil immediately after installation.

Before applying oils, please consult a specialized salesman and adhere to the enclosed instruction, or let the application of oils to a specialized company trained in doing so.

SPECIAL FEATURES

Requirements of ÖNORM S 1555 regarding perspiration and saliva resistance as well as standards ÖNORM EN 71.3 „Safety of toys.Migration of certain parts („with no heavy metals content“) are met. Our floors meet the requirements of R10 anti-slip class pursuant to BGR 181 (before known as ZH1/571) and DIN 51130.

CLEANING/MAINTENANCE

Our floors should be cleaned for the first time 14 days after installation by water or soft cleaning agent suitable for oiled wooden floors. (Adler Natumah Reiniger 80055). If you want to remove grease, you can use ADLER Legno-Öl 50880 ff. For renovation and/or colour revitalization, perform one application and remove the remaining oil. Please, adhere to the Instruction for treatment of oiled product with Adler Legno-Öl 50880 ff.

INSTALLATION

Installation

BK Parket wooden floors must be glued by suitable parquet glue through overall application or by means of application of rows of glue directly to hard surface.

Construction for under floor heating 12mm (oak oak oak) is suitable for installation to areas with under floor heating.

Sport and dance floors should be installed by means of stapling into a suitable grille.

Before installation

It is necessary to make sure that the area used for installation is sufficiently dry and aired. The base must be dry (maximum humidity is 2%, and relative air humidity should not exceed 65%). The floor should be placed into the area appr. 48hours before installation. Temperature during installation should not fall below 10°C.

The deviation from evenness of the base must not exceed 2mm through 2m in all directions, otherwise adjustment must be done through concrete application before the installation. Especially with anhydride bases, we hereby recommend sanding the base before glueing and applying subsequent penetration surface treatment in order to ensure correct adhesion to the bottom side of the floor.

Warning

When installing floor to a system of under floor heating you must provide for adjustment curve and the technology of installation must comply to the requirements of the floor producer and supplier of glues.

BEFORE USE

Before you start using the floor, let the glue dry and harden for at least 12 hours by preventing the contact with the floor. Heavy furniture and interior decorations should only be laid down after 24 hours following the installation.

Warning

Wooden floor is not subject to warranty if the installation has not been done properly or if you failed to act in accordance with producer recommendations. It is recommended to leave the installation to specially trained personnel.

SUITABILITY OF USE

Any residential objects except bathrooms, showers, winter gardens or wet areas. Suitable for commercial premises, restaurants, bars, hotel lounges, reception areas, showrooms and studios. Construction suitable for under floor heating 12 mm /oak oak oak/ is suitable for use with the under floor heating.

Sports and dance floor is suitable for sports halls, tennis and squash centres, especially for basketball and other ball indoor games and dance rooms.

Warning

Wooden floor BK Parket should be installed in premises with the environment temperature 16-23°C and relative air humidity 45-65 °C. Adequate safety should be ensured in order to prevent damage by furniture. It is recommended to use specialized filters and pads for furniture legs.

Also, safety mats are recommended to prevent scratches and standing water.

In case any liquid is spilt on the floor, dry the floor immediately to prevent the penetration of liquid through surface pores deeper into the parquet.

